



ECOMISTER
EVAPORATOR



HD19 EcoMister Evaporator

HD19 EcoMister Evaporator

All units in the HD series are designed to operate in the harshest environments 24 hours a day, 365 days a year, and are available in **land based**, trailer based and float-based configurations depending on your specific needs. Pump packages are also available to match the needs of your site along with wind sensing automated control systems.

BENEFITS AND FEATURES

Longevity in the Harshest Environments

The HD19 EcoMister is built with our patented stainless-steel axial flow turbine and our stainless-steel directional wind tunnel and both are coated with specially blended 3M™ Scotchkote™ for durability against the elements and to meet the corrosive conditions of operating sites. Motors are built to exceed IEEE-841 Severe Duty standards and are 3rd party tested to guarantee a 0.5 mil vibration rate to maximize the motor's operational lifetime.

Fits the Smallest Ponds

With the smallest turbine of the three evaporator sizes the HD19 offers the smallest plume for those sites with limited space. Still equipped with a dynamically balanced aluminum fan and our directional air delivery tube which creates laminar air flow, the spray pattern is engineered to reduce water particle collision and to reach maximum loft or "hang time". This longer "hang time" along with a specifically engineered droplet size maximizes your evaporation efficiency, even on a smaller pond.

Low Operating Costs

To maximize efficiency and minimize operational costs the turbine is spun to a specific size allowing for manufacturing tolerances of fewer than 30 thousandths of an inch. This allows the turbine to operate at lower horsepower requirements but provides air volumes comparable to a much larger and more costly unit. Systems are designed for minimal maintenance and down time through thoughtful design like simplified greased ports on the motors to a quick release camlock on the nozzle ring manifold.

Flexibility

Each evaporator is available in multiple base configurations including fixed land based, trailer based, and float based, providing the best solutions and setup for the needs of each site. A simplified pitch adjustment system allows the operator to easily adjust the direction and angle of the wind tunnel to optimize plume control and evaporation efficiency in varying site conditions.

Specifications

- Max Horizontal Throw from Machine (Length) is 50 FT (15 M)
- Annual Disposal Volume at 50% Efficiency is 22,700 Cubic Meters (6,000,000 US Gallons)
- Manufactured from a carefully selected combination of stainless steel and carbon steel
- All wetted components are Stainless Steel
- Our 19" enhanced evaporation fan
- A robust coating system, Scotchkote™ 134 powder coat
- Custom designed electric motor that exceeds IEEE841 standards,
- equipped with a stainless-steel motor shaft (HD) and specialty corrosion resistant paint
- Dual independent fan support bearings separated by vibration coupling which does not allow thrust/vibration to transfer from fan thrust and/or fan vibration to the motor
- System is vibration tested to ensure optimal and long lasting operation
- Powder coated Aluminum fan. It is also available in Stainless steel for extremely severe corrosion applications
- Attention to detail during manufacturing with stringent quality control
- Quick release nozzle ring with **Teflon nozzles**
- Pump volume throughput unit is **6.5 m³/hr at 690 kPa (28.6 US GPM at 100 PSI)**
- Average weight of land base unit is **450 kg (1,000 lbs)**
- **WARRANTY:** All units have a minimum one-year parts and labor warranty, 2 years on IEEE841 motors



Figure 1 - HD19 EcoMister Evaporator (with custom tank)